

Model: **MARS9H**



**MARS9H**



**MARS9H-AS**

Part Number	MARS9H	MARS9H-AS	
<b>Image Sensor</b>	Pixels	9M	9M
	Resolution	4250*2160	4250*2160
	Frame Rate@Full Resolution	300	300
	Frame Rate@Partial Resolution	4250*696@800FPS	4250*696@800FPS
	Resolution	4250*272@2000FPS	4250*272@2000FPS
	Frame Rate Adjustment	Adjustable	Adjustable
	Latency(ms)	3.00	3.00
	Type of Exposure	global	global
<b>Track Performance and Range</b>	Exposure Speed	Settable	Settable
	Accuracy	+/-0.05mm	+/-0.05mm
	Observation Distance(with 15mm diameter markers) <sup>[1][2]</sup>	28m	Affected by sunlight intensity
	Active Marker Supported	Yes	Yes
<b>Camera</b>	Lens Specification	8mm	8mm
	Field of View(FOV)	68°*37°	68°*37°
	Aperture Adjustable	Yes	Yes
	Focus Adjustable	Yes	Yes
<b>LEDs</b>	Number <sup>[3]</sup>	22	22
	Type	HLED	HLED
	Brightness Adjustable	Yes	Yes
	Wavelength	850nm	850nm
<b>Interface and Power Supply</b>	Connection Type	GigE/POE	GigE/POE
	Power Consumption	25W	25W
	Sync Interface	3.5mm AUX	3.5mm AUX
	Sync Signal Output	Optional	Optional
<b>Product Appearance and Operating Conditions</b>	Shell Material	Metal	Metal
	Size	126*104*142mm	126*104*142mm
	Weight	1.052kg	1.052kg
	Mounting Hole	1/4"	1/4"
	Number of Mounting Holes	2	2
	Temperature Range	-20°C to 65°C	-20°C to 65°C
	Humidity	< 80%	< 80%
<b>Others</b>	Outdoor	No	Suitable for sunlight use
	Packaging	Eco-friendly, simple carton packaging	
	Integration	Flexible, standard network cable connections for easy adaptability to different usage scenarios	
Heat Dissipation	Fanless passive heat dissipation structure, for silent operation, minimal dust accumulation, and optimal heat dissipation		

**Key Features**

- Lightweight metal shell, effortless installation with versatile mounting options for diverse and challenging environments.
- Seamless integration with force plates, EMG devices, and more through TTL triggering.
- In-house research and development ensuring outstanding quality control and dedicated after-sales support.

Note

- [1] Observation distance depends on marker diameter.
- [2] To increase distance, add light source, use bigger or active markers.
- [3] LED number is customizable.

